




24" monitor with an integrated web camera and microphone

The XB2472HSUC is a high-end desktop monitor for demanding users looking for a high quality screen assuring seamless compatibility with any video or web conferencing software. The VA matrix offers wide viewing angles and sharp contrast. The blue light reducer function with flicker free LCD technology reduces eye strain and offers a more comfortable viewing experience. Supplied with a height-adjustable stand featuring swivel and pivot functions, allows you to adjust the position of the screen to your preferences. Furthermore, the versatile connectivity options assure cross platform compatibility (VGA, DVI, DisplayPort and USB hub) and make the XB2472HSUC the right panel to choose for your connected workplace.



WEBCAM & MICROPHONE

Integrated web camera and microphone assure seamless compatibility with any video or web conferencing applications.



HAS + PIVOT

With a height adjustable stand you will create an ergonomic work posture and position that meets all health and safety requirements. This will not only prevent any health issues but will also increase your productivity. The pivot function allows the screen to rotate from landscape to portrait orientation. This functionality can be useful if the application requires more height than width.

1. DISPLAY CHARACTERISTICS

DIAGONAL	23.6"; 59.8cm
ASPECT RATIO	16 : 9
PANEL	VA LED, matte finish
NATIVE RESOLUTION	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
BRIGHTNESS	250 cd/m ² typical
CONTRAST	3 000 : 1 typical
CONTRAST	12 000 000 : 1 ACR
RESPONSE TIME	8 ms
VIEWING ZONE	horizontal/vertical: 178° / 178° ; right/left: 89° / 89° ; up/down: 89° / 89°
DISPLAY COLOUR	16.7 million
BLUE LIGHT REDUCER	yes
FLICKER FREE LED	yes
DISPLAY AREA H X W	293.2 x 521.28 mm; 11.5" x 20.5"
PIXEL PITCH H X V	0.2715 x 0.2715 mm
HORIZONTAL SYNC	30 - 94 KHz
VERTICAL SYNC	50 - 75 Hz
SYNCHRONIZATION	Separate sync

2. INTERFACES & CONNECTORS

ANALOG INPUT CONNECTOR	VGA
DIGITAL INPUT CONNECTOR	DVI, DisplayPort
HDCP	yes;
HEADPHONE CONNECTOR	Yes
OUTPUT CONNECTOR	headphone connector
USB HUB	UP 1 x USB 2.0 / DOWN 2 x USB 2.0

3. FEATURES

APPLE - MAC	All iiyama monitors are compatible with Apple-Macintosh computers.
PLUG & PLAY	VESA DDC2B™
CONTROLS	Via OSD in 9 languages (EN, DE, FR, IT, NL, PL, RU, ES, CZ) and 5 front controls (Power, Menu, Scroll up/ Volume, Scroll down/ ECO, Input/ Select)
USER CONTROLS	picture (brightness, contrast, H. position, V. position, phase, clock, colour temp., auto adjust), OSD (H. position, V. position, timeout, transparency), display (display mode, i-Style Colour, ACR, X-Res Technology, sharpness, OD, gamma, blue light reducer), audio settings (volume, mute, audio input), miscellaneous (language, input select, opening logo, after AC cut, ECO mode, reset), information
SPEAKERS	2 x 2 W (Stereo)
ANTI-THEFT-DEVICE	Kensington-lock™ prepared
CERTIFICATES	CE, TUV-Bauart, CU

EXTRA FUNCTIONS	integrated webcam (2.0 megapixel) and microphone
HEIGHT ADJUSTABLE STAND	Yes
HEIGHT ADJUSTMENT	130 mm
ROTATION (PIVOT FUNCTION)	90°
SWIVEL STAND	180°; 90° left; 90° right
TILT ANGLE	22° up; 5° down
VESA MOUNTING	100 x 100 mm
COLOUR	Black

4. ACCESSORIES

INCLUDED ACCESSORIES	power cable, DisplayPort cable, USB cable, stand, quick start guide, safety guide
----------------------	---

5. POWER MANAGEMENT

POWER SUPPLY	AC 100 - 240 V, 50 / 60 Hz
POWER SUPPLY UNIT	internal
POWER USAGE	21.5 W typical; max. 0.5 W in Power management mode
POWER MANAGEMENT	VESA DPMS, ENERGY STAR®

6. EPEAT SILVER

EPEAT	EPEAT is a comprehensive environmental rating that helps identify greener computers and other electronic equipment. The Silver certification means the monitor meets all required criteria plus at least 50% of the optional requirements. EPEAT Silver is valid in countries where iiyama registers the product. Please visit www.epeat.net for the registration status in your country.
-------	--

7. DIMENSIONS & WEIGHT

DIMENSIONS W X H X D	557 x 406.5 (536.5) x 230 mm
WEIGHT	5.8 kg

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION (). ALL RIGHTS RESERVED.