

3 Port SuperSpeed USB 3.0 Hub with Gigabit Ethernet

StarTech ID: ST3300U3S



The ST3300U3S USB 3.0 Hub features an integrated Gigabit Ethernet adapter, enabling you to add 3 additional USB 3.0 ports as well as an RJ45 Gigabit Ethernet port, through a single SuperSpeed USB 3.0 connection to the host computer system.

With Gigabit Ethernet NIC support, connect to your home or office network at full bandwidth, with support for 10/100/1000Mbps networks, unlike USB 2.0 adapters.

Backwards compatible with USB 2.0 and USB 1.x standards, this USB 3.0 Hub with Gigabit Ethernet will still support older USB devices and can also be used in an older system that does not have USB 3.0 ports (speed limited by USB bus).

Charge multiple mobile devices, such as Apple® and Android devices, conveniently and quickly through a single USB 3.0 port on your computer

With the capability to mix and match USB 3.0/2.0/1.x devices and be used with or without the included external power adapter, this hub offers the best of versatility and portability.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Connect a wide variety of peripherals at home/office to a laptop and be able to instantly disconnect them all from a single USB connection
- Replace a failed integrated network adapter with an external, USB Ethernet connection, instead of having to open a desktop or laptop computer case
- Quickly charge multiple mobile devices, such as iPhone®/iPad®/iPod®/Android devices through a single USB 3.0 port

Features

- 3 SuperSpeed USB 3.0 ports with up to 5Gbps of bandwidth
- Fully compliant with USB 3.0 rev 1.0 specifications with up to 5Gbps of available bandwidth
- Backward compatible with USB 2.0 and USB 1.0/1.1 devices
- Supports USB 3.0/2.0/1.x devices simultaneously, at full bandwidth
- Plug-and-Play and hot-swap compatible
- 10/100/1000 Mbps RJ45 Ethernet port
- Fully compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab and IEEE 802.3az specifications
- Supports Auto-MDIX, Wake-on-LAN and Jumbo Frames
- Crossover Detection & Auto-Correction (Auto MDIX)

Technical Specifications

Warranty	2 Years
Bus Type	USB 3.0
Chipset ID	ASIX AX88179 + VIA VL811
Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az
Industry Standards	USB 3.0 rev. 1.0
Interface	USB 3.0
Connector Type(s)	1 - RJ-45 Female
Connector Type(s)	1 - USB 3.0 Micro-B (10 pin; SuperSpeed) Female
Connector Type(s)	3 - USB 3.0 A (9 pin; SuperSpeed) Female
Auto MDIX	Yes
Compatible Networks	10/100/1000 Mbps
Full Duplex Support	Yes
Maximum Data Transfer Rate	5 Gbps (USB 3.0) 1 Gbps (Gigabit Ethernet)
Type and Rate	USB 2.0 - 480 Mbit/s
Type and Rate	USB 3.0 - 5 Gbit/s
OS Compatibility	Windows XP(32/64-bit)/ Server 2003(32/64-bit)/ Server 2008 R2/ Vista(32/64-bit)/ 7(32/64-bit)/ 8 (32/64-bit) Mac OS 10.x Linux
Product Height	15 mm [0.6 in]
Product Length	75 mm [3 in]
Product Weight	75 g [2.6 oz]
Product Width	55 mm [2.2 in]
LED Indicators	1 - Blue - Power
LED Indicators	1 - Green - Network Link (solid) / Activity (flashing)
Center Tip Polarity	Positive
Input Voltage	Universal 115 ~ 230 AC
Output Current	2
Output Voltage	5 DC
Plug Type	M
Power Adapter Included	Yes
Humidity	5% ~ 85% RH
Operating Temperature	0°C ~ 50°C (32°F ~ 122°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)

Package Quantity	1
Shipping (Package) Weight	155 g [5.5 oz]
Included in Package	1 - USB 3.0 Hub
Included in Package	1 - Micro USB 3.0 Cable
Included in Package	1 - Universal Power Adapter
Included in Package	3 - Power Adapter Plug (NA/ UK/ EU)
Included in Package	1 - Driver CD
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

