

Mobile SATA Spinpoint M8



Capacity		320GB	500GB	750GB	1TB
Model	8 MB	HN-M320MBB	HN-M500MBB	HN-M750MBB	HN-M101MBB

FEATURES

- Max. 500GB formatted capacity per disk
- SATA Native Command Queuing Feature
- TuMR/PMR head with FOD technology
- Serial ATA 3.0Gbps Interface Support
- Load/Unload Head Technology
- ATA Security Mode Feature Set
- ATA S.M.A.R.T. Feature Set
- SilentSeek™
- NoiseGuard™

DRIVE CONFIGURATION

Capacity ¹	320 / 500 / 750GB, 1TB
Interface	SATA 3.0 Gbps (1.5Gbps)
Buffer DRAM Size ²	8 MB
Rotational Speed	5,400 RPM class

PERFORMANCE SPECIFICATIONS

Average Seek time (typical)	12 ms
Average Latency	5.6 ms
Data Transfer Rate	
Media to/from Buffer (Max.)	145 Mb/s
Buffer to/from Host (Max.)	300 MB/s
Drive Ready Time (typical) ³	4 sec

RELIABILITY SPECIFICATIONS

Non-recoverable Read Error	1 sector in 10 ¹⁴ bits
Controlled Ramp Load/Unload	600,000

ACOUSTICS

Idle	2.4 Bel
Performance Seek	2.6 Bel

POWER REQUIREMENTS

Voltage	+5V±5%
Spin-up Current (Max.)	1000 mA
Seek (AVG) ⁴	2 W
Read/Write (AVG)	2.2 W
Low Power Idle (AVG)	0.7 W
Standby (AVG)	0.2 W
Sleep (AVG)	0.2 W

ENVIRONMENTAL SPECIFICATIONS

Temperature	
Operating	5 ~ 55 °C
Non-operating	-40 ~ 70 °C
Humidity (non-condensing)	
Operating	5-90 %
Non-operating	5-95 %
Linear Shock (1/2 sine pulse)	
Operating, 2ms	325 G
Non-operating, 2ms	750 G
Vibration (swept sine, 1/4 octave per minute)	
Operating	1.5 Grms
Altitude (relative to sea level)	
Operating	-300 to 3000 m
Non-operating	-400 to 15000 m

PHYSICAL DIMENSION

Height	9.5 ± 0.2 mm
Width	69.75 ± 0.25 mm
Length	100.3 ± 0.4 mm
Weight (max.)	107 g

* Note : Design and specifications are subject to change without prior notice.

1.1MB = 1,000,000 Bytes, 1GB = 1,000,000,000 Bytes

Accessible capacity may vary as some OS uses binary numbering system for reported capacity

2 A small portion of the 8MB buffer memory is reserved for firmware use

3 Power-On to Drive Ready

4 30% duty cycle, random seek

