

1 Port USB over Cat5 / Cat6 Ethernet Extender - up to 131ft (40m)

StarTech ID: USB110EXT2



The USB110EXT2 USB 1.1 Extender enables you to extend a USB 1.1 connection over distances of up to 40-meters (131-feet) using standard Cat5 or Cat6 UTP cabling, bypassing the normal limitation of 5m (15ft) for USB 1.1 devices and allows for the host computer system to be safely stored in a remote location.

The USB Extender features a compact design with no external power requirements, making it the ideal solution for remote USB cameras, keyboards, mice or other input devices for environments where install space or access to electrical outlets is limited.

Able to deliver up to 300mA of power (when supplied with 500mA from the host computer), the extender is fully compliant with the USB 1.1 specification, with support for up to 12Mbps of data bandwidth.

Backed by a StarTech.com 3-year warranty and free lifetime technical support.

Applications

- Secured environments where the host computer must be in a secure, inaccessible location from the the keyboard, mouse, camera or other USB input devices
- Use existing in-wall Cat5/Cat6 wiring to extend USB 1.1 device connections between rooms
- Reduce cable clutter and the need for mid-point USB hubs/repeaters by running a single, easy-to-install Cat5/Cat6 cable
- Industrial control environments where the host computer must be located away from interference or contamination

Features

- 1x USB 1.1 port, 1x RJ45 port
- Support for a maximum distance of up to 40m (131ft), over Cat5 or Cat6 cabling
- Full Speed USB 1.1 compliant host interface, with data bandwidth up to 12 Mbps
- Efficient circuit design provides up to 300mA of power at the remote end
- 8kV Contact and 16kV Air Electrical Static Discharge (ESD) protection
- Integrated USB cables
- No driver or software required

Technical Specifications

Warranty	3 Years
Ports	1
Cabling	Cat 5e UTP or better
Local Unit Connectors	1 - RJ-45 Female
Local Unit Connectors	1 - USB A (4 pin) Male
Remote Unit Connectors	1 - RJ-45 Female
Remote Unit Connectors	1 - USB A (4 pin) Female
Maximum Data Transfer Rate	12 Mbps
Max Distance	40 m / 131 ft
OS Compatibility	Windows 2000/ XP(32/64-bit)/ Server 2003(32/64-bit)/ Vista(32/64-bit)/ 7(32/64-bit)/ Server 2008 R2/8(32/64-bit), Windows CE 6.0, and Mac OS X, and Linux
Color	Black
Enclosure Type	Plastic
Product Length	85 mm [3.3 in]
Product Width	40 mm [1.6 in]
Product Height	25 mm [1 in]
Product Weight	50 g [1.8 oz]
Power Adapter Included	USB Powered
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Humidity	20% ~ 80% RH
System and Cable Requirements	Available USB port
Package Quantity	1
Shipping (Package) Weight	185 g [6.5 oz]
Included in Package	1 - USB 1.1 Extender Local Unit

Included in Package 1 - USB 1.1 Extender Remote Unit

Included in Package 1 - Instruction Manual

Certifications, Reports and Compatibility

