

Backup PFC Sinewave Series

CP1300EPFCLCD/1500EPFCLCD

PFCD0012AU-02

The Most Affordable Pure Sine Wave UPS Ever

CyberPower[®]
Reliability. Quality. Value.

The CyberPower PFC Sinewave UPS with pure sine wave output safeguards mid- to high-end computer systems, servers and networking hardware that use conventional and Active Power Factor Correction (PFC) power supplies while the featured RJ11/RJ45 port ensures phone, fax, and modem lines are protected from surges. With Automatic Voltage Regulation (AVR) stabilizes the AC signal and maintains a safe voltage, this allows the UPS to maintain safe power levels for the connected equipment without resorting to battery power. The multifunction LCD readout provides immediate access to precise information of critical power/battery condition.

The included PowerPanel[®] Personal Edition management software showcases the featured rich abilities such as input/output power voltage readings, self-diagnostics, and approximate battery backup time. With the patented GreenPower UPS[™] Technology offers clean and stable battery backup, PFC Sinewave Series can save up to 75% of electricity therefore save your electricity expenses.



Applications

- Home and Home Office
- Home Theater System
- Small Office
- Medium Business

Series Features

- GreenPower UPS[™] Technology
- Automatic Voltage Regulator (AVR)
- EMI, RFI, Surge and Spike Protection
- Phone/Fax/Modem/DSL/Network Protection
- Auto-Restart/Auto-Charge
- LCD Status Monitor
- USB & Serial Connectivity Ports
- USB Charging Ports
- User-Replaceable Batteries
- PowerPanel[®] Personal Edition Software

Energy-Saving


PFC Compatible

Surge Protection

Phone Line Protection

LCD Display

USB Charging Ports



Front

Back

ACTIVE PFC POWER SUPPLIES COMPATIBLE



The PFC Sinewave Series protects equipments with Active PFC power supplies from unexpected shutdown or harmful stress when switching from AC power to UPS battery power.

PowerPanel[®] Personal Edition Management S/W



AUTO-SHUTDOWN SOFTWARE

CyberPower PowerPanel[®] Personal Edition Management Software, is compatible with Windows7, Vista, XP, 2000 Pro., ME, 98, Windows Server 2008, 2003, Mac and Linux.

**Software functions may vary due to firmware version and/or hardware constraints.*

Backup PFC Sinewave Series

CP1300EPFCLCD/1500EPFCLCD

CyberPower[®]
Reliability. Quality. Value.

Technical Specification

Model	CP1300EPFCLCD	CP1500EPFCLCD
Configuration		
Capacity (VA / Watts)	1300 / 780	1500 / 900
Energy-Saving Technology	Yes	
Input		
Frequency Range	47 Hz – 63 Hz (Auto Sensing)	
Input Plug Type	IEC 320 C14	
Output		
UPS Outlets (Numbers)	(3) Battery Backup & Surge Protected Outlets (3) Full-Time Surge Protected Outlets	
On Battery Output Voltage	Pure Sine Wave at 230 Vac +/- 10%	
On Battery Output Frequency	50 Hz / 60 Hz +/- 1%	
Transfer Time (Typical)	4ms	
Overload Protection	On utility: Internal Current Limiting & Circuit Breaker On battery: Internal Current Limiting	
AVR	Yes	
Surge Protection and Filtering		
Surge Protection	Yes	
DSL/Phone/Fax/Modem Protection	RJ45 x 2 (One In / One Out)	
Physical		
Dimensions (H x W x D) (mm)	265 x 100 x 370	
Weight (kg)	9.5	10.9
Battery		
Sealed Maintenance Free Lead Acid Battery	12V / 7AH x 2	12V / 8.5.AH x 2
User Replaceable	Yes	
Typical Recharge Time	8 Hours	
Status Indicators		
Indicators	Power On	
Audible Alarms	Battery Discharge, Battery Low, Overload (Battery Mode), Fault	
Multi-function LCD Readout	Yes	
Communication		
PowerPanel® Personal Edition	Windows 7 / Vista / XP / 2000, Server 2008 / 2003, Linux	
Management		
Auto-Charge / Auto-Restart	Yes	
Connectivity Ports	USB, Serial	

#All specifications are subject to change without notice. ©2012 CyberPower Systems. All Trademarks are the property of their owners.

Packaging Content:



Product Unit



USB Cable



Phone Cable



AU Power Cord



IEC Power Cord



User Manual



Warranty Card



Software CD



DISTRIBUTED BY:

CyberPower's
Manufacturing
Facilities are
ISO 9001:2008,
ISO 14000, and
QC080000
Approved