

# USB 2.0 to 10/100 Mbps Ethernet Network Adapter Dongle

StarTech ID: USB2100



The USB2100 USB 2.0 to 10/100 Mbps Network Adapter lets you add a Fast Ethernet port to your laptop or desktop computer through USB.

This compact USB network adapter offers a dongle design with a built-in cable to avoid cramped connections, making it a perfect solution for adding wired Ethernet connectivity to your desktop without opening the case, or to replace a failed onboard network adapter on your laptop system.

Providing half or full-duplex operation, this USB 2.0 Ethernet adapter supports data transfer rates of up to 200 Mbps. The adapter also supports features such as Wake-on-LAN (WoL) and VLAN tagging for added flexibility.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### **Applications**

- Add a 10/100 Mbps Ethernet port to any desktop or laptop without opening the case
- Replacement for a failed onboard Ethernet port on a desktop or laptop

#### **Features**

- 10/100 Mbps Ethernet through USB 2.0
- IEEE 802.3i and 802.3u (10BASE-T, 100BASE-TX) compatible
- Supports half / full-duplex operation
- Crossover Detection & Auto-Correction (Auto MDIX)
- IEEE 802.1Q VLAN Tagging support
- Dongle with integrated USB cable



### **Technical Specifications**

Warranty 2 Years

Ports 1

USB Pass-Through No

Interface RJ45 (10/100 Ethernet)

Bus Type USB 2.0

Industry Standards IEEE802.3i, IEEE 802.3u

Chipset ID ASIX - AX88772C

Connector Type(s) 1 - USB A (4 pin) Male

Connector Type(s) 1 - RJ-45 Female

Compatible Networks 10/100 Mbps

Maximum Data Transfer Rate 200 Mbps (Ethernet - Full-Duplex)

Max Distance 100 m / 330 ft

Type and Rate USB 2.0 - 480 Mbit/s

Auto MDIX Yes
Full Duplex Support Yes

OS Compatibility Windows® 8 / 8.1 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64)

Windows Server® 2012, 2008 R2, 2003(32/64)

Mac OS® 10.x (Tested up to 10.9)

Google Chrome OS™

Linux 2.6.x / 3.x (Tested up to 3.5)

System and Cable Requirements Available USB port

Color Black Enclosure Type Plastic

Cable Length 150 mm [5.9 in]
Product Length 66 mm [2.6 in]
Product Width 22 mm [0.9 in]
Product Height 17 mm [0.7 in]
Product Weight 49 g [1.7 oz]
LED Indicators 1 - Link
LED Indicators 1 - Activity

Operating Temperature 10°C to 40°C (50°F to 114°F)
Storage Temperature -20°C to 70°C (-4°F to 158°F)

Humidity 10~90% RH Shipping (Package) Weight 85 g [3 oz]

Included in Package 1 - USB 2.0 Fast Ethernet Adapter

Included in Package 1 - Driver CD

Included in Package 1 - Instruction Manual





## Certifications, Reports and Compatibility















